



CRESTAKYD[®] 30-5004

Short oil air drying alkyd

INTRODUCTION

Crestakyd 30-5004 is a short oil alkyd, based on a semi-drying oil for rapid air drying industrial paints and low bake enamels.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	%	60
Solvent		xylene
Acid Value (base resin)	mg KOH g ⁻¹	7 max
Colour PRS		1.25 max
Viscosity (25°C) (PRS bubble tube)	mPa s	4250
Flash Point (Theoretical)	°C	24

APPLICATIONS

Crestakyd 30-5004 is a fast drying short oil alkyd resin designed for industrial coating applications. The use of standard metal driers is recommended with this resin. For air drying applications a suitable starting point will be 0.05% cobalt, 0.2% zirconium calculated as metal on resin solids.

PACKAGING

Crestakyd 30-5004 is supplied in metal drums. Bulk deliveries are supplied by road tanker.

STORAGE

Crestakyd 30-5004 can be stored in containers supplied. Where practical store the product below it's flash point.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No.2

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

