

CRESTAKYD[®] 10-3507

Long oil alkyd

INTRODUCTION

CRESTAKYD 10-3507 is a high solids, fast drying alkyd that has excellent brushability & flow characteristics, as well as good gloss retention & weathering resistance.

CHARACTERISTICS (Not to be taken as a specification)

Solids content	%	75
Oil type		Linoleic
Oil content	%	62
Solvent		aliphatic naphtha
Acid value (base resin)	mgKOHg- 1	12 max
Viscosity, Brookfield Spindle 3, 10 rpm at 25°C	mPa·s	5250
Colour	Gardner	6 max

APPLICATIONS

CRESTAKYD 10-3507 can be used for decorative gloss paints and varnishes.

PACKAGING

CRESTAKYD 10-3507 can be supplied in drums. Bulk deliveries are by road tanker.

STORAGE

CRESTAKYD 10-3507 The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

HEALTH & SAFETY

Please see separate material safety data sheet.

Issue No. 5 Oct-16

All information on this data sheet is based on laboratory testing and is not intended for design purposes. Scott Bader makes no representations or warranties of any kind concerning this data. Due to variance of storage, handling and application of these materials, Scott Bader cannot accept liability for results obtained. The manufacture of materials is the subject of granted patents and patent applications; freedom to operate patented processes is not implied by this publication.

SCOTT BADER COMPANY LIMITED

Wollaston, Wellingborough, Northamptonshire, NN29 7RL

Telephone: +44 (0) 1933 663100

Facsimile: +44 (0) 1933 666623

www.scottbader.com