

CRYSTIC[®] 2000PA

General Purpose Polyester Resin

Introduction

Crystic 2000PA is a preaccelerated, general purpose unsaturated polyester resin. It has been specifically designed for non-critical applications. Laminating can be carried out by hand-lay or spray application. Crystic 2000PA is available in a coloured version, and the information contained in this leaflet also applies to this resin. It cannot be colour matched to specific requirements.

Applications

For normal mouldings made with chopped strand mat, a resin to glass ratio of about 2-2.5:1 should be achievable with Crystic 2000PA.

Variants

Crystic 2000PA is also available as a coloured version.

Formulation

Crystic 2000PA is formulated for room temperature curing applications. It requires only addition of the correct amount of Andonox[®] KP9 catalyst to start the curing reaction. The recommended formulation is given in table 1.

Table 1: Formulation for curing Crystic 2000PA

Component	Parts by weight
Crystic 2000PA	100
Andonox [®] KP9 or Norox [®] MEKP925H	1.0 - 3.0

The catalyst must be stirred thoroughly into the resin shortly before use. Curing should not be carried out at temperatures below 15°C. Scott Bader (Pty) Ltd. will not be liable for problems caused by use at lower temperatures than recommended. The resin must be allowed to attain workshop temperature (15-30°C) before being formulated for use.

N.B. Peroxide catalysts are highly reactive and may decompose with explosive violence, or cause fires, if they come into contact with flammable materials, metals or accelerators. For this reason they must never be stored in metal containers or be mixed directly with accelerators.

Crystic 2000PA is formulated for use between 15°C and 30°C. It is recommended that workshop temperatures be maintained within this range.

At temperatures above 30°C, the gel time even at 1% Catalyst M can be so short that there is insufficient working time to use up all the resin that has been mixed. In such cases, do not use less than 1% catalyst as this can cause undercure. Rather use Norox[®] MEKP-925H. If using 1% Norox[®] MEKP-925H still gives too short a working time, do not use less than this. Rather mix smaller quantities of resin at a time so that it can all be used within the working time available.

At temperatures below 15°C, the curing reaction can be so slow that there is a high probability of undercure of the resin, even with over 2.5% Andonox[®] KP9. Do not use more than 3% catalyst as that will not speed up the geltime appreciably or result in a faster cure; in fact it can further retard the cure. Rather warm up the resin and working area so that it is above 15°C.

Additives

Crystic 2000PA is supplied in two versions - clear and coloured. Moulders can add their own pigment pastes to the clear version if required. However, no guarantees can be given concerning colour reproducibility from batch to batch. Any additions of fillers or pigments may adversely affect the properties of the resin. Users should satisfy themselves that any additions to the resin will not affect their requirements.

Post curing

Satisfactory laminates for non-critical applications can be made with Crystic 2000PA by curing at workshop temperature (25°C).

Typical Properties

Table 2: Typical liquid properties of Crystic 2000PA.

Property	Units	Nominal value
Viscosity at 25°C: Brookfield RVT sp. 3 at 100rpm	centipoise	400
Thixotropic index	ratio	1.5
Appearance	visual	Opaque
Stability at 25°C	months	3
Geltime at 25°C using 1% Andonox® KP9 catalyst	minutes	24

Storage

Crystic 2000PA should be stored in the dark in suitable closed containers. It is recommended that the storage temperature should be less than 25°C where practical, but should not exceed 30°C. Ideally, containers should be opened only immediately prior to use. Where they have to be stored outside, it is recommended that drums be kept in a horizontal position to avoid the possible ingress of water.

Packaging

Crystic 2000PA is supplied in 25kg kegs and 225kg drums. Bulk supplies can be delivered by road tanker.

Health and Safety

Please see the applicable Material Safety Data Sheets, depending on the curing system used.

Technical Leaflet No. SBPTY089.0

Version 2 : February 2013

All information on this data sheet is based on laboratory testing and is not intended for design purposes. Scott Bader makes no representations or warranties of any kind concerning this data. Due to variance of storage, handling and application of these materials, Scott Bader cannot accept liability for results obtained. The manufacture of materials is the subject of granted patents and patent applications; freedom to operate patented processes is not implied by this publication.

SCOTT BADER COMPANY LIMITED

Wollaston, Wellingborough, Northamptonshire, NN29 7RL

Telephone: +44 (0) 1933 663100

Facsimile: +44 (0) 1933 666623

www.scottbader.com