



# CRESTACRYL<sup>®</sup> 71-5060

## Thermoplastic acrylic resin

**INTRODUCTION** CRESTACRYL 71-5060 is a thermoplastic acrylic resin, which gives rapid solvent release, very good elasticity, excellent adhesion on various metallic substrates and very good alkali and water resistance.

### CHARACTERISTICS

Solids content	50 ± 2%
Solvent	Xylene
Viscosity, 40%NVS in X, Brookfield, @ 25°C, sp3/10rpm	1500 - 3000 mPa s
Gardner Colour	max. 2

**APPLICATION** CRESTACRYL 71-5060 can be used for primers, paints for metal and finishes for wood.

**PACKAGING** CRESTACRYL 71-5060 can be supplied in drums and in containers on special request.

**STORAGE** The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided

**HEALTH & SAFETY** Please see separate material safety data sheet.

Issue No. 1



CROATIA, 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: [info@scottbader.hr](mailto:info@scottbader.hr)

