



CRESTACRYL[®] 71-9078

Thermoplastic acrylic resin

INTRODUCTION CRESTACRYL 71-9078 is a high quality thermoplastic acrylic resin, which gives rapid solvent release, very good elasticity, excellent adhesion on various metallic substrates and very good alkali and water resistance.

CHARACTERISTICS

Solids content, 150°C/60min	50 ± 2%
Solvent	Butyl Acetate
Brookfield, @ 23°C, sp3/10rpm	3 000 – 5 000 mPa s
Colour, APHA	max. 200 Hazen

APPLICATION CRESTACRYL 71-9078 can be used as universal binder for metal paints, wood coatings, road marking paints, masonry paints and concrete.
Metal protective coatings have good adhesion on ferrous and non-ferrous metals.
Road-marking paints and concrete coatings have good durability, abrasion resistance and good resistance to yellowing.

PACKAGING CRESTACRYL 71-9078 can be supplied in drums, containers and bulk on request.

STORAGE The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided

HEALTH & SAFETY Please see separate material safety data sheet.

Issue No. 2



CROATIA , 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: info@scottbader.hr

