



# CRESTAKYD<sup>®</sup> 10-1022

Long oil air drying alkyd

Previous Name: CHROMOSAL SU-67 70WS

**INTRODUCTION** CRESTAKYD 10-1022 is a fast drying alkyd that has excellent brushability & flow characteristics, as well as good gloss retention & weathering resistance.

## CHARACTERISTICS

Solid content	70±1,5%
Oil Type	Linoleic rich
Oil content	67%
Solvent	White Spirit
Acid values (base resin)	max. 10 mgKOH/g
Efflux time, 50%NVS in WS, DIN cup 4, @ 20°C	70 - 100s
Gardner Colour	max. 6

**APPLICATION** CRESTAKYD 10-1022 can be used for economical decorative and do-it-yourself paints, including primers, topcoats, and varnishes.

**PACKAGING** CRESTAKYD 10-1022 can be supplied in drums, road-tankers and in containers.

**STORAGE** The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided

**HEALTH & SAFETY** Please see separate material safety data sheet.

Issue No. 1



CROATIA, 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: [info@scottbader.hr](mailto:info@scottbader.hr)

