



CRESTAKYD[®] 10-2505

Long oil air drying alkyd

Previous Name: CHROMOSAL SU-67 LV WS180/220

INTRODUCTION CRESTAKYD 10-2505 is a fast drying alkyd that has excellent brushability & flow characteristics, as well as good gloss retention & weathering resistance.

CHARACTERISTICS

Solid content	80 ± 1,5%
Oil Type	Linoleic rich
Oil content	67%
Solvent	non-aromatic White Spirit 180/220, D60
Acid values (base resin)	max. 10 mgKOH/g
Viscosity, 80%NVC, @ 25°C, sp3/10rpm	2500 - 4000mPas
Gardner Colour	max. 7

APPLICATION CRESTAKYD 10-2505 can be used for economical decorative and do-it-yourself paints, including primers, topcoats, and varnishes.

PACKAGING CRESTAKYD 10-2505 can be supplied in drums, road-tankers and in containers.

STORAGE The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided

HEALTH & SAFETY Please see separate material safety data sheet.

Issue No. 2



CROATIA, 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: info@scottbader.hr

