



 **SCOTT BADER**

CRESTAKYD[®] 20-9509

Medium oil air drying alkyd

INTRODUCTION CRESTAKYD 20-9509 is a high solids, medium oil alkyd based on linoleic rich fatty acids supplied in butyl acetate and designed for use in wood coating finishes.

CHARACTERISTICS

Solid content	75 ± 1,5%
Oil Type	Linoleic
Oil content	50%
Solvent	Butyl Acetate
Acid values (base resin)	max. 30 mgKOH/g
Viscosity @ 25°C, sp 3/10rpm	1 500 . 3 000 mPas
Colour, Gardner	max. 8

ADDITIONAL INFORMATION

OH-number (base resin)	150 mgKOH/g
------------------------	-------------

APPLICATION CRESTAKYD 20-9509 has been designed for use in high solids acid curing finishes for wood. Coating systems based on this resin exhibit fast cure, excellent pot-life and good wet heat resistance.

PACKAGING CRESTAKYD 20-9509 can be supplied in drums, road-tankers and in containers.

STORAGE The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided

HEALTH & SAFETY Please see separate Material Safety Data Sheet

Issue No. 1/14.11.2016

 **SCOTT BADER d.o.o.**

CROATIA , 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: info@scottbader.hr

