



CRESTAKYD®30-5049 Short oil alkyd

INTRODUCTION

CRESTAKYD 30-5049 is a short oil alkyd based on linoleic rich fatty acids supplied in

xylene and designed for use in wood coating applications.

CHARACTERISTICS

Acid values (base resin) max. 25 mgKOH/g Viscosity @ 25°C, sp3/10rpm 2 500 . 4 500 mPas

Colour, Gardner max. 7

ADDITIONAL INFORMATION

Relative density @ 20°C 1,02g/cm³

APPLICATION CRESTAKYD 30-5049 has been designed for use in acid curing finishes for wood.

This resin provides excellent cold check properties, good wet heat resistance, good

stackability and excellent all round properties

PACKAGING CRESTAKYD 30-5049 can be supplied in drums, road-tankers and in containers.

STORAGE The resin should be stored in the original, unopened and undamaged containers in a

dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should

be avoided

HEALTH & SAFETY Please see separate Material Safety Data Sheet

Issue No. 1/14.11.2016



CROATIA, 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: info@scottbader.hr





