



# CRESTAKYD<sup>®</sup> 30-5067

## Short oil air drying alkyd

**INTRODUCTION** CRESTAKYD 30-5067 is a fast drying short oil alkyd supplied in xylene for use in air-dry and force-dry primers and topcoats.

### CHARACTERISTICS

Solids content	60 ± 1,5%
Oil Type	Linoleic rich
Oil content	28%
Solvent	Xylene
Acid Value, 100%	max. 10 mgKOH/g
Viscosity, Brookfield @ 25°C sp3 / 10rpm	3000 . 6000 mPa s
Gardner Colour, DF	max. 7

**APPLICATION** CRESTAKYD 30-5067 is recommended for use in air-dry and force-dry primers and topcoats in a variety of general industrial metal coating applications.

**PACKAGING** CRESTAKYD 30-5067 can be supplied in drums, road-tankers and in containers..

**STORAGE** The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided

**HEALTH & SAFETY** Please see separate material safety data sheet.

Issue No. 1/14.11.2016



CROATIA , 10000 ZAGREB, Radnička cesta 173i.

tel.: +385 1 2406-440

fax: +385 1 2404-573; +385 1 2404-926

e-mail: [info@scottbader.hr](mailto:info@scottbader.hr)

