

## Technical Data Sheet

### INTRODUCTION

Crestapol® 1261 is a modified version of Crestapol® 1260 with an extended open/ worktime. It is a low viscosity urethane acrylate type resin which is suitable for infusion, Resin Transfer Moulding (RTM) and similar processes at room temperature, and can be infused at vacuum levels down to -1.0 Bar. Crestapol 1261 produces laminates with high strength and toughness with exceptional water and hydrolysis resistance.

### KEY FEATURES OF CRESTAPOL® 1261

- ▶ Excellent mechanical performance and durability using only moderate temperature post-curing cycles
- ▶ High temperature performance - HDT 109°C/ 228°F and Tg 112°C/ 234°F
- ▶ Compatible with carbon fibre reinforcement materials and general purpose sizing agents
- ▶ Ability to vary cycle time eliminates the need to stock different resin grades
- ▶ Standard 60 minute gel time but also available in 30 minute gel time

### FORMULATION

Crestapol® 1261 should be allowed to attain workshop temperature before use. For curing at room temperature Crestapol 1261 requires the addition of a catalyst and an accelerator.

**N.B.** Catalysts and accelerators should not be mixed directly together, since they react with explosive violence.

The recommended catalyst for curing at room temperature is Cumyl Hydroperoxide, which should be added at 2% into the resin and thoroughly dispersed. The recommended accelerator is 1% solution of cobalt in styrene, which should be added at 2% into the resin and thoroughly dispersed.

### POST CURING

Satisfactory laminates for many applications can be made using Crestapol® 1261 by curing at workshop temperature. For high temperature post cure, temperatures of over 80°C will be required to reach full cure. If you have any further questions contact a member of the Scott Bader tech service team.

### PHYSICAL DATA – UNCURED

The following tables give typical properties of Crestapol® 1261 when tested in accordance with BS2782.

| Property  | Unit              | Crestapol® 1261             |
|---|-------------------|-----------------------------|
| Appearance  | -                 | Clear yellowish brown resin |
| Viscosity at 25°C 4500 sec <sup>-1</sup>  | Poise             | 2.25                        |
| Density at 25°C   | gcm <sup>-3</sup> | 1.038 - 1.042               |
| Stability from date of manufacture when stored in accordance with storage recommendations | Months            | 12                          |
| Working time*   | Mins              | 40 - 50                     |

\*at 20°C 2% of 1% solution cobalt in styrene, 2% Cumyl Hydroperoxide. Curing Schedule - 24 hrs at 20°C, 3 hrs at 80°C.

## PHYSICAL DATA - CURED: PURE CAST RESIN SHEET

| Property             | Unit                   | Crestapol® 1261  |
|----------------------|------------------------|--|
| Barcoal hardness     | -                      | 55   |
| HDT                  | °C/ °F                 | 109/228  |
| Tensile strength*    | MPa                    | 76   |
| Tensile modulus*     | GPa                    | 3.6  |
| Elongation at break* | %                      | 2.7  |
| CTE - Alpha 1        | ppm (°C) <sup>-1</sup> | 65   |
| CTE - Alpha 2        | ppm (°C) <sup>-1</sup> | 200  |
| Tg - TMA             | °C<br>°F               | 100 (onset), 112 (Tg) and 125 (exit)<br>212 (onset), 234 (Tg) and 257 (exit) |

\*at 20°C 2% of 1% solution cobalt in styrene, 2% Cumyl Hydroperoxide. Curing Schedule - 24 hrs at 20°C, 3 hrs at 80°C.

## STORAGE

Crestapol® 1261 should be stored between 5°C and 25°C in the original, unopened container in a dry, well ventilated place. Protect from freezing and direct sunlight. Avoid contact with oxidising agents. If stored outside of these recommendations, shelf life will be significantly reduced.

## PACKAGING

Crestapol® 1261 is supplied in 25kg (6.6 gallon), 200kg (53 gallon) and 1000kg (264 gallon) containers.

## HEALTH & SAFETY

Please see separate Material Safety Data Sheet.



*Making a positive difference*

© 2020 ScottBader Co Ltd, May 2020

All information on this data sheet is based on laboratory testing and is not intended for design purposes. Scott Bader makes no representations or warranties of any kind concerning this data. Due to variance of storage, handling and application of these materials, Scott Bader cannot accept liability for results obtained. The manufacture of materials is the subject of granted patents and patent applications; freedom to operate patented processes is not implied by this publication.

### Scott Bader UK

Wollaston, Wellingborough, Northants  
NN29 7RL, UK

Tel: +44 (0)1933 666738

Email: [enquiries@scottbader.com](mailto:enquiries@scottbader.com)