



PRODUCT OVERVIEW

TEXICRYL® 13-065 is a styrene acrylic copolymer emulsion, designed primarily as a binder for high performance ceramic tile adhesives.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	50%
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	65 mPa s
pH	8
Particle size	200 nm
Emulsifying system	anionic/nonionic
Minimum film formation temperature**	26 °C
Glass transition temperature	29 °C

*Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-065 has been designed to be formulated with a wide range of filler types into water resistant tile adhesives and fix and grouts.

PACKAGING AND STORAGE

TEXICRYL 13-065 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-065 should be stored in the original, unopened and undamaged containers. Exposure to frost and extended sunlight should be avoided.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com

Scott Bader UK Office

Wollaston
Wellingborough
Northants
NN29 7RL
UK

Tel: +44 (0)1933 666738

email: enquiries@scottbader.com