



Technical Data Sheet

PRODUCT OVERVIEW

TEXICRYL® 13-066 is a styrene acrylic copolymer emulsion, designed primarily for the production of flexible, water-resistant ceramic tile adhesives.

TEXICRYL 13-066 is especially suitable for floor tile adhesive.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	50%
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	700 mPa s
pH	8
Particle size	200 nm
MFFT*	0 °C
Glass Transition Temperature	4 °C

*Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-066 can be compounded into adhesives with a high degree of flexibility for use with wall and floor ceramic tiles.

PACKAGING AND STORAGE

TEXICRYL 13-066 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-066 should be stored in the original, unopened and undamaged containers. Exposure to frost and extended sunlight should be avoided.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com



Scott Bader UK Office

Wollaston
Wellingborough
Northants
NN29 7RL
UK

Tel: +44 (0)1933 666738

email: enquiries@scottbader.com