

Acrylic Dispersions



Technical Data Sheet

PRODUCT OVERVIEW

TEXICRYL® 13-070 is a styrene-acrylic copolymer emulsion designed primarily as a binder for D1 ceramic tile adhesives.

CHARACTERISTICS (Not to be taken as a specification)	
Solids content	50%
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	90 mPa s
рН	8.5
Particle size	250 nm
Specific gravity at 25°C	1.05
Minimum film formation temperature*	24 ℃
Glass transition temperature	34 ℃

^{*}Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-070 has been designed to be formulated, with a wide range of filler types, into D1 tile adhesives.

PACKAGING AND STORAGE

TEXICRYL 13-070 is be supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-070 should be stored in the original, unopened and undamaged containers. Exposure to frost and extended sunlight should be avoided.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com



Scott Bader UK Office

Wollaston Wellingborough Northants NN29 7RL UK

Tel: +44 (0)1933 666738 email: enquiries@scottbader.com

© 2020 ScottBader Co Ltd, August 2020 $\,\mid\,\,$ Issue No. 1