



Technical Data Sheet

PRODUCT OVERVIEW

TEXICRYL® 13-073 is a styrene acrylic copolymer emulsion, designed primarily for the production of flexible, water-resistant ceramic tile adhesives.

TEXICRYL 13-073 is especially suitable for floor tile adhesives.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	50%
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	750 mPa s
pH	8
Particle size	150 nm
Specific gravity at 25°C	1.03 g/cm ³
Minimum film formation temperature*	0 °C
Glass transition temperature	8 °C

*Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-073 can be compounded into adhesives with a high degree of flexibility for use with wall and floor ceramic tiles.

PACKAGING AND STORAGE

TEXICRYL 13-073 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-073 should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Exposure to frost should be avoided.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com

Scott Bader UK Office

Wollaston
Wellingborough
Northants
NN29 7RL
UK

Tel: +44 (0)1933 666738

email: enquiries@scottbader.com