



Technical Data Sheet

PRODUCT OVERVIEW

TEXICRYL® 13-078 is a styrene acrylic copolymer emulsion, designed primarily as a binder for high performance ceramic tile adhesives.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	50%
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	100 mPa s
pH	8.3
Particle size	250 nm
Minimum film formation temperature*	18 °C
Glass transition temperature	20 °C

*Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-078 has been designed to be formulated with a wide range of filler types into water resistant tile adhesives and grouts.

PACKAGING AND STORAGE

TEXICRYL 13-078 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-078 should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Exposure to frost should be avoided.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com

Scott Bader UK Office

Wollaston
Wellingborough
Northants
NN29 7RL
UK

Tel: +44 (0)1933 666738

email: enquiries@scottbader.com