



PRODUCT OVERVIEW

TEXICRYL® 13-308 is an alkali soluble emulsion designed as a thickener for water-based formulations.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	30.5%
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	25 mPa s
pH	3
Particle size	200 nm
Specific gravity at 25°C	1.07 g/cm ³
Minimum film formation temperature*	0 °C
Glass transition temperature	57 °C

*Determined by metal bar with temperature gradient

APPLICATION

TEXICRYL 13-308 can be used in the formulation of ceramic tile adhesives, paints and waterborne coating systems.

PACKAGING AND STORAGE

TEXICRYL 13-308 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-308 should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Exposure to frost should be avoided.

HEALTH AND SAFETY

Please see separate material safety data sheet.

www.scottbader.com

Scott Bader UK Office

Wollaston
Wellingborough
Northants
NN29 7RL
UK

Tel: +44 (0)1933 666738

email: enquiries@scottbader.com