



## Technical Data Sheet

### PRODUCT OVERVIEW

TEXICRYL® 13-317 is a hydrophobically modified alkali swellable thickener designed for water-based formulations. It is very effective at high shear rates showing Newtonian rheology characteristics in formulated systems with excellent film build and levellin.

#### CHARACTERISTICS

(Not to be taken as a specification)

Solids content	30%
Viscosity at 25°C (Brookfield RVT, Spindle 2, 100 rpm)	30 mPa s
pH	2.5
Specific gravity at 25°C	1.06
Particle size	100 nm

### APPLICATION

TEXICRYL 13-317 has been designed for use in the formulation of waterborne coatings and architectural or decorative paints.

### PACKAGING AND STORAGE

TEXICRYL 13-317 is supplied in drums or IBC's (please check with your local representative). Bulk deliveries are by road tanker.

TEXICRYL 13-317 should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Exposure to frost should be avoided

### HEALTH AND SAFETY

Please see separate material safety data sheet.

[www.scottbader.com](http://www.scottbader.com)

#### Scott Bader UK Office

Wollaston  
Wellingborough  
Northants  
NN29 7RL  
UK

Tel: +44 (0)1933 666738

email: [enquiries@scottbader.com](mailto:enquiries@scottbader.com)